

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 2 Issued July 2004

RA 2532 ECONOMY DOUBLE-SIDED TISSUE TAPE EASY-RELEASE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Hot Melt		
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.075	mm
180 degree peel adhesion:		
Open side	1400	N/m
Closed side	1400	N/m
Polyester loop tack:		
Open side	1300	N/m
Closed side	1300	N/m
Liner release	10	N/m
Tensile strength	1200	N/m
Elongation at break	10	%
Service temperature	-15 to +75	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>80	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road, Wednesbury, WS10 7TN, UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797