

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 6 Issued August 2005

RA 2012 DOUBLE-SIDED GENERAL PURPOSE TISSUE TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier	0.105	mm
Release liner thickness	0.065	
180 degree peel adhesion: Open side	1000	N/m
Closed side	1000	N/m
Polyester loop tack: Open side	900	N/m
Closed side	900	N/m
Liner release	10	N/m
Tensile strength	1100	N/m
Elongation at break	4	%
Service temperature	-40 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	Greater than 50	Hours
Shelf life	12	Months
Test Methods: BS 7116		BS 7116

**This product is also available in fingerlift form.
Standard formats 6/12, 9/15, 12/18, 18/24, 24/30. Other formats, including offset fingerlift
available subject to minimum order quantities.**

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Est, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797