

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 6 Issued Feb 2007

### RA 2056 DOUBLE-SIDED HIGH TACK TISSUE TAPE

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier	0.085	mm
Release liner thickness	0.055	mm
180 degree peel adhesion: Open side	1100	N/m
Closed side	1100	N/m
Polyester loop tack: Open side	1000	N/m
Closed side	1000	N/m
Liner release	15	N/m
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature	-40 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	> 50	Hours
Shelf life	12	Months

Test Methods: BS 7116

Standard fingerlift formats

6/12, 9/15, 12/18, 18/24, 24/30  
Other formats, inc. offset fingerlift  
available subject to min. quantities

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797