

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 6

Issued May 16

### RA 2063 DOUBLE-SIDED TISSUE TAPE HIGH TACK, HIGH COAT WEIGHT / NORMAL TACK

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier	0.100	mm
Release liner thickness	0.055	mm
180 degree peel adhesion: Open side	1300	N/m
Closed side	1000	N/m
Polyester loop tack: Open side	1200	N/m
Closed side	1000	N/m
Liner release	10	N/m
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +23	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	4	Hours
Shelf life	12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd  
Wednesbury. West Midlands. WS10 7TN  
Tel: +44(0)121-525 5151 Fax: +44 (0)121-568 6797  
Email: sales@paladhesives.co.uk