200 SERIES TECHNICAL DATA

PAL ADHESIVE PRODUCTS Ltd

Product datasheet Issue No 6 Issued July 2008

RA 2068 DOUBLE-SIDED POLYPROPYLENE TAPE
120gsm WHITE RELEASE LINER

TECHNICAL DETAILS		TYPICAL VALUE	UNITS
Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin			
Thickness, adhesive + carrier		0.08	mm
Release liner thickness		0.110	mm
180 degree peel adhesion:	Open side	1000	N/m
	Closed side	1000	N/m
Polyester loop tack:	Open side	1000	N/m
	Closed side	1000	N/m
Liner release		10	N/m
Tensile strength		1600	N/m
Elongation at break		75	%
Service temperature		-10 to +60	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>100	Hours
Shelf life		12	Months

Test Methods: BS 7116

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.**

PAL ADHESIVE PRODUCTS Ltd
Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568 6797