200 SERIES TECHNICAL DATA

PAL ADHESIVE PRODUCTS Ltd

Product datasheet Issue No 5 Issued Oct 2010

RA 2069 DOUBLE-SIDED TISSUE TAPE
120gsm Glassine release liner

TECHNICAL DETAILS		TYPICAL VALUE	UNITS
Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin			
Thickness, adhesive + carrier		0.090	mm
Release liner thickness		0.125	mm
180 degree peel adhesion:	Open side	1000	N/m
	Closed side	1000	N/m
Polyester loop tack:	Open side	900	N/m
	Closed side	900	N/m
Liner release		10	N/m
Tensile strength		1000	N/m
Elongation at break		4	%
Service temperature		-10 to +60	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>100	Hours
Shelf life		12	Months

Test Methods: BS 7116

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETEMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.**

PAL ADHESIVE PRODUCTS Ltd
Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568 6797