

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 4 Issued Nov 15

RA 2075 DOUBLE-SIDED POLYPROPYLENE FILM TAPE HIGH ADHESIVE COAT WEIGHT

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier	0.110	mm
Release liner thickness	0.055	mm
180 degree peel adhesion: Open side	1300	N/m
Closed side	1300	N/m
Polyester loop tack: Open side	1200	N/m
Closed side	1200	N/m
Liner release	10	N/m
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	2	Hours
Shelf life	12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121-568-6797