

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Provisional datasheet Issue No. 2

Issued Mar 15

RA 2362 DOUBLE-SIDED BLACK FILMIC HI-VIS (EASY VISIBILITY SPLICING TAPE)

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.120

mm

Release liner thickness

0.055

mm

180 degree peel adhesion:

Open side
Closed side

1100
1100

N/m
N/m

Polyester loop tack:

Open side
Closed side

1200
1200

N/m
N/m

Liner release

10

N/m

Tensile strength

500

N/m

Elongation at break

100

%

Service temperature

-10 to +60

Deg. C

Recommended application temperature

+5 to +25

Deg. C

Shear adhesion, 1 Kg @ 23 deg. C

>100

Hours

Shelf life

12

Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston, Wednesbury, WS10 7SG UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 505 1487