

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 3 Issued January 2015

RA 2557 DOUBLE-SIDED POLYPROPYLENE TAPE EASY-RELEASE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type	Hot Melt Rubber Resin	
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.080	mm
180 degree peel adhesion:		
Open side	1000	N/m
Closed side	1000	N/m
Polyester loop tack:		
Open side	1100	N/m
Closed side	1100	N/m
Liner release	10 max.	N/m
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	Greater than 100	Hours
Shelf life	12	Months
Test Methods: BS 7116		
FDA Approval	Specification 175.105	

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road industrial Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 505 1487