

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 2 Issued Feb 2016

RA 2712 DOUBLE-SIDED GENERAL PURPOSE TISSUE TAPE 50M FILMIC LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.105

mm

Release liner thickness

0.050

180 degree peel adhesion: Open side
 Closed side

1000

N/m

1000

N/m

Polyester loop tack: Open side
 Closed side

900

N/m

900

N/m

Liner release

10

N/m

Tensile strength

1100

N/m

Elongation at break

4

%

Service temperature

-40 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

Greater than 50

Hours

Shelf life

12

Months

Test Methods: BS 7116

BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797