

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 6 Issued August 14

RA 2732 DOUBLE-SIDED TISSUE TAPE ECONOMY GRADE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive type: Pressure-sensitive hotmelt rubber/resin

Thickness, adhesive + carrier

0.080

mm

Release liner thickness

0.055

mm

180 degree peel adhesion: Open side
 Closed side

N/A

N/m

N/A

N/m

Polyester loop tack: Open side
 Closed side

1200

N/m

1200

N/m

Liner release

10

N/m

Tensile strength

1200

N/m

Elongation at break

10

%

Service temperature

-10 to +60

Deg. C.

Recommended application temperature

+5 to +60

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

50

Hours

Shelf life

12

Months

Test Methods: BS 7116

This product is also available in fingerlift form.

Standard formats 6/12, 9/15, 12/18, 18/24, 24/30. Other formats, including offset fingerlift available subject to minimum order quantities.

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Industrial Estate, Darlaston. WS10 7TN

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797

Email: sales@paladhesives.co.uk