

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 1 Issued Jan 2010

### RA 2757 DOUBLE-SIDED POLYPROPYLENE TAPE 50m PET FILMIC LINER

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type: Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.080

mm

Release liner thickness

0.050

mm

180 degree peel adhesion:    Open side  
  Closed side

1000

N/m

1000

N/m

Polyester loop tack:            Open side  
  Closed side

1000

N/m

1000

N/m

Liner release

10 max.

N/m

Tensile strength

2200

N/m

Elongation at break

75

%

Service temperature

-10 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

Greater than 100

Hours

Shelf life

12

Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY. ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN, UK.

Email: [sales@paladhesives.co.uk](mailto:sales@paladhesives.co.uk)

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797