

3000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 3 Issued September 2015

RA 3012 DOUBLE-SIDED TISSUE TAPE MODIFIED ACRYLIC ADHESIVE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Emulsion Acrylic

Thickness, adhesive + carrier
Release liner thickness

0.080
0.070

mm
mm

180 degree peel adhesion: Open side
 Closed side

750
750

N/m
N/m

Polyester loop tack: Open side
 Closed side

850
850

N/m
N/m

Liner release

10

N/m

Tensile strength

1000

N/m

Elongation at break

4

%

Service temperature

-20 to +120

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

20

Hours

Shelf life

12

Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 505-1487