

3000 SERIES

TECHNICAL DATA



Product datasheet Issue No 2 Issued Nov 2010

RA 3568 DOUBLE-SIDED POLYESTER FILM TAPE

Pure Acrylic adhesive; 120gsm glassine release liner

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.070	mm
Release liner thickness	0.125	mm
180 degree peel adhesion:		
Open side	400	N/m
Closed side	400	N/m
Polyester loop tack:		
Open side	800	N/m
Closed side	800	N/m
Liner release	10	N/m
Tensile strength	4600	N/m
Elongation at break	12	%
Service temperature	-20 to +140	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	100	Hours
Shelf life	12	Months
Test Methods:		BS 7116

.THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
.DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Est, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121-568 6797

