

PRODUCTS TECHNICAL DATA

Issue No 4 Issued Dec 2012

RAS 68129 DOUBLE-SIDED PVC FOAM TAPE SECURITY GLAZING TAPE INDEPENDENTLY TESTED TO BS 7950

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive type	Acrylic	
Adhesive coat weight (total)	70	gsm
Liner type	Glassine paper, Amber	
Foam density	200	Kg per cu metre
Shore Hardness (00 Scale)	40	
Force to compress to 25%	0.63	Kg per squ cm
Tensile strength MD	550	kPa
Elongation at break MD	160	%
Liner release	10 max.	N/m
Service temperature	-20 to +90	Deg. C.
UV resistance	Excellent	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	
Recommended application temperature	+10 to +40	Deg. C
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury
West Midlands, WS10 7TN U.K.

Tel: +44 (0)121-526 5151 Fax: +44 (0)121-568-6797