

PRODUCTS TECHNICAL DATA

Issue No. 2

Issued July 2016

RAS 78161 SINGLE-SIDED PVC FOAM GLASS PROTECTION PADS, COLOUR GREY

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive type	Solvent Acrylic	
Adhesive coat weight	10	g per sq. m.
Nominal foam density	200	Kg/ cu.m.
Available thicknesses	3.0 4.5	mm
Shore Hardness	50	00 scale
Force to compress 25%		Kg per sq. cm.
Tensile strength	550	kPa
Elongation at break	160	%
Service temperature, short term	-20 to +90	Deg. C.
long term	-20 to +50	Deg. C.
Recommended application temperature	+10 to +45	Deg. C.
UV resistance	Excellent	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797