

PRODUCTS TECHNICAL DATA

PAL ADHESIVE
PRODUCTS Ltd

Product data sheet Issue No. 3 Issued June 2016

RA 8625C DOUBLE-SIDED POLYETHYLENE FOAM TAPE ACRYLIC ADHESIVE, 1.0mm THICK BLACK

<u>TECHNICAL DETAILS</u>		<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive plus foam		1.10	mm
Release liner thickness		0.90	mm
Release liner type		White PE coated	
Foam type		Crosslinked Polyethylene	
Foam density		85	Kg/cu.m.
180 deg. Peel adhesion:	Open side	700	N/m
	Liner side	700	N/m
Polyester loop tack:	Open side	800	
	Liner side	800	
Liner release		10	N/m
Tensile strength,	M.D.	1450	kPa
	C.D.	985	kPa
Elongation at break	M.D.	275	%
	C.D.	325	%
Service temperature		-40 to +70 long term -40 to +90 short term	Deg. C Deg. C
Recommended application temperature		+5 to +25	Deg. C
Shelf life		12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 - 6797