

PRODUCTS TECHNICAL DATA

Product data sheet Issue No. 2 Issued June 2016

RA8625G DOUBLE-SIDED POLYETHYLENE FOAM TAPE ACRYLIC ADHESIVE, 1.0mm THICK BLACK

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive plus foam		1.10	mm
Release liner thickness		0.100	mm
Release liner type		Green PE Film	
Foam type		Crosslinked Polyethylene	
Foam density		85	Kg/cu.m.
180 deg. Peel adhesion:	Open side	1600*	N/m
	Liner side	1600*	N/m
Polyester loop tack:	Open side	1200*	N/m
	Liner side	1200*	N/m
Shear adhesion, 1Kg 25mm sq.		*Mixture of peel/foam tear 10	hours
Liner release		10	N/m
Tensile strength,	M.D.	1215	kPa
	C.D.	775	kPa
Elongation at break	M.D.	225	%
	C.D.	275	%
Service temperature		-40 to +70 long term	Deg. C
		-40 to +90 short term	Deg. C
weather resistance		Excellent - suitable for outdoor use	
Recommended application temperature		+5 to +25	Deg. C
Shelf life		12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568- 6797