

# 1000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Issue No. 6

Issued Feb 2016

### RA 1100 SOLVENT ACRYLIC TRANSFER TAPE

( Amber Release liner)

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Thickness of adhesive	0.03	mm
Release liner; Amber - double sided glassine	80	g per sq.m.
Adhesive coat weight	30 - 35	g per sq. m.
Peel adhesion*	600	N/m
Polyester loop tack	1250	N/m
Liner release	10 max.	N/m
Shear adhesion failure temperature (SAFT)	85 - 90	Deg. C.
Recommended application temperature	+5 to +25	Deg.C.
Service temperature range	-20 to +90	Deg. C.
UV resistance	Excellent	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	

Test Methods: BS 7116

\* Value quoted after 10 mins dwell time

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury  
West Midlands, WS10 7TN U.K.

Tel: +44 (0)121-526 5151 Fax: +44 (0)121- 568-6797

Email: sales@paladhesives.co.uk