200 SERIES TECHNICAL DATA

PAL ADHESIVE PRODUCTS Ltd

Product datasheet Issue No. 6 Issued December 2003

RA 2013 REINFORCED TRANSFER TAPE
OPEN DIAGONAL SCRIM PATTERN

TECHNICAL DETAILS		TYPICAL VALUE	UNITS
Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin			
Thickness, adhesive + carrier		0.090	mm
Release liner thickness		0.065	
180 degree peel adhesion:	Open side	1100	N/m
	Closed side	1100	N/m
Polyester loop tack:	Open side	1300	N/m
	Closed side	1300	N/m
Liner release		20	N/m
Tensile strength		400	N/m
Elongation at break		25	%
Service temperature		-20 TO +65	Deg. C.
Recommended application temperature		+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		50	Hours
Shelf life		12	Months
Test Methods: BS 7116			

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.**

PAL ADHESIVE PRODUCTS Ltd
Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk