

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 6 Issued October 15

RA 2038 TRANSFER TAPE (HEAVY COAT WEIGHT)

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt /
Rubber Resin

Thickness, adhesive + carrier
Release liner thickness

0.075

mm

0.055

mm

180 degree peel adhesion: Open side

1250

N/m

Polyester loop tack: Open side

1250

N/m

Liner release

20

N/m

Service temperature

-10 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

50

Hours

Shelf life

12

Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797