

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 8 Issued May 16

RA 2065 DOUBLE-SIDED GENERAL PURPOSE FINGERLIFT TISSUE TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier		0.085	mm
Release liner thickness		0.055	mm
180 degree peel adhesion:	Open side	1000	N/m
	Liner side	1000	N/m
Polyester loop tack:	Open side	1100	N/m
	Liner side	1100	N/m
Liner release		10	N/m
Tensile strength		1100	N/m
Elongation at break		4	%
Service temperature		-10 to +60	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
Static shear adhesion, 1Kg @ 23 deg. C.		Greater than 100	Hours
Shelf life		12	Months
Standard product formats		6/12, 9/15, 12/18, 18/24, 24/30 Other formats, inc. offset fingerlift available subject to min quantities	mm
FDA Approval		175.105	
Test Methods: BS 7116			

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568 6797