

# PRODUCTS TECHNICAL DATA

Product datasheet Issue No. 1 Issued Dec 12

## RA2120 Reinforced Transfer tape PET Square Scrim

### TECHNICAL DETAILS

### TYPICAL VALUE

### UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier \*  
Thickness adhesive only

0.09  
0.07

mm  
mm

180 degree peel adhesion  
Open side  
Closed side

1100  
1100

N/m  
N/m

Polyester Loop tack  
Open side  
Closed side

1200  
1200

N/m  
N/m

Release from self

10

N/m

Service temperature

-10 to + 60

Deg C.

Recommended application temperature

+5 to +25

Deg C.

Shear adhesion 1Kg @23 deg C.

50

Hours

Shelf Life

12

Months

Test Methods

BS7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: [sales@paladhesives.co.uk](mailto:sales@paladhesives.co.uk)

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797