

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 1 Issued June 2010

RA 2304 PERMANENT REINFORCED TRANSFER TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier 0.070 mm

Release liner type White Glassine Liner
Release liner thickness 0.055 mm

180 degree peel adhesion: Open side 1200 N/m
Closed side 1400 N/m

Polyester loop tack: Open side 1400 N/m
Closed side 1100 N/m

Liner release 10 N/m

Service temperature -40 to +60 Deg. C.

Recommended application temperature +5 to +25 Deg. C.

Shelf life 12 Months

Test Methods: BS 7116

This product has been tested internally and would show to be an "acid free" product

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797