

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Issue number 1

Issued Oct. 2004

### RA 2336 REINFORCED PEELEABLE ACRYLIC TRANSFER TAPE

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Thickness adhesive plus carrier		0.060	mm
Release liner type		White glassine	
Release liner thickness		0.065	mm
Peel adhesion to steel:	Open side	120	N/m
	Liner side	120	N/m
Polyester loop tack	Open side	240	N/m
	Liner side	240	N/m
Liner release		10	N/m
Service temperature range		-10 to +100	Deg. C.
Recommended application temperature		+5 to +25	Deg. C
Shelf life		12	Months
Test Methods: B S 7116			

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.  
Email: sales@paladhesives.co.uk  
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797