

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 9 Issued Feb 2014

### RA 2735 DOUBLE-SIDED ECONOMY FINGERLIFT TISSUE TAPE, WHITE LINER

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.080

mm

Release liner thickness

0.055

180 degree peel adhesion:    Open side  
  Closed side

900  
900

N/m  
N/m

Polyester loop tack:        Open side  
                                      Closed side

1000  
1000

N/m  
N/m

Liner release

10

N/m

Tensile strength

1200

N/m

Elongation at break

10

%

Service temperature

-10 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

Greater than 100

Hours

Shelf life

12

Months

Standard product formats

6/12, 9/15, 12/18, 18/24, 24/30  
Other formats, inc. offset fingerlift  
available subject to min. quantities

Test Methods

BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 505 1487