

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 1 Issued December 2005

RA 2742 DOUBLE-SIDED GLASS FIBRE SCRIM TAPE POLYESTER FILM RELEASE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

| | | |
|-------------------------------------|------------|---------|
| Thickness, adhesive + carrier | 0.170 | mm |
| Release liner thickness | 0.050 | mm |
| 180 degree peel adhesion: Open side | 1200 | N/m |
| Closed side | 1200 | N/m |
| Polyester loop tack: Open side | 1300 | N/m |
| Closed side | 1300 | N/m |
| Liner release | 10 | N/m |
| Service temperature | -10 to +60 | Deg. C. |
| Recommended application temperature | +5 to +25 | Deg. C. |
| Shear adhesion, 1Kg @ 23 deg. C. | 50 | Hours |
| Shelf life | 12 | Months |

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797