

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 1 Issued November 2013

RA 2813F DOUBLE-SIDED POLYESTER FILM - BAG SEAL TAPE FILMIC RELEASE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive High Tack Hot Melt Grade

Thickness, adhesive + carrier

0.085

mm

Release liner thickness

0.050

mm

Film colours available

Clear,pink,blue,white

180 degree peel adhesion: Open side
 Closed side

1300
1300

N/m
N/m

Polyester loop tack: Open side
 Closed side

1400
1400

N/m
N/m

Liner release

10

N/m

Tensile strength

4600

N/m

Elongation at break

120

%

Service temperature

-10 TO +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

>100

Hours

Shelf life

12

Months

Test Methods: BS 7116

The individual ingredients of the the adhesive have been tested and approved for indirect food contact to the FDA specification 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd