

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 1 Issued April 2015

RA 2823F DOUBLE-SIDED POLYPROPYLENE FILM - BAG SEAL TAPE FILMIC RELEASE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type : Pressure Sensitive High Tack Hot Melt Grade

Thickness, adhesive + carrier	0.085	mm
Release liner thickness	0.050	mm

Film colours available	Clear, Pink, Blue, White	
------------------------	--------------------------	--

180 degree peel adhesion:	Open side	1300	N/m
	Closed side	1300	N/m

Polyester loop tack:	Open side	1400	N/m
	Closed side	1400	N/m

Liner release	10	N/m
---------------	----	-----

Tensile strength	4600	N/m
------------------	------	-----

Elongation at break	120	%
---------------------	-----	---

Service temperature	-10 TO +60	Deg. C.
---------------------	------------	---------

Recommended application temperature	+5 to +25	Deg. C.
-------------------------------------	-----------	---------

Shear adhesion, 1Kg @ 23 deg. C.	>100	Hours
----------------------------------	------	-------

Shelf life	12	Months
------------	----	--------

Test Methods: BS 7116

The individual ingredients of the the adhesive have been tested and approved for indirect food contact to the FDA specification 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd