

# 3000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 2 Issued Jan 2004

### RA 3054 DOUBLE-SIDED POLYESTER FILMIC TAPE MODIFIED ACRYLIC ADHESIVE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.070	mm
Release liner thickness	0.070	mm
180 degree peel adhesion:    Open side	750	N/m
Closed side	750	N/m
Polyester loop tack:            Open side	850	N/m
Closed side	850	N/m
Liner release	10	N/m
Tensile strength	4600	N/m
Elongation at break	12	%
Service temperature	-20 to +120	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	20	Hours
Shelf life	12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.  
Email: sales@paladhesives.co.uk  
Tel: +44 (0)121 - 526 5151                      Fax: +44(0)121- 568 6797