

# 3000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No 2

Issued Jan 2004

### RA 3055 DOUBLE-SIDED POLYESTER FILMIC TAPE MODIFIED ACRYLIC ADHESIVE HIGH PERFORMANCE

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Thickness, adhesive + carrier	0.110	mm
Release liner thickness	0.070	mm
180 degree peel adhesion: Open side	850	N/m
Closed side	850	N/m
Polyester loop tack: Open side	900	N/m
Closed side	900	N/m
Liner release	10	N/m
Tensile strength	4600	N/m
Elongation at break	12	%
Service temperature	-20 to +120	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	20	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.

Email: [sales@paladhesives.co.uk](mailto:sales@paladhesives.co.uk)

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797