

3000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 3 Issued July 2015

RA 3222 PERM/PEEL FILMIC, HIGH-TACK OPEN SIDE DOUBLE-SIDED TAPE, WHITE PAPER LINER

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.050	mm
Release liner thickness	0.055	mm
Adhesive types	Liner side Acrylic, open side hotmelt	
180 degree peel adhesion: Open side	1000	N/m
Closed side	150	N/m
Polyester loop tack: Open side	1000	N/m
Closed side	100	N/m
Liner release	10	N/m
Tensile strength	4600	N/m
Elongation at break	12	%
Service temperature	-20 TO +60	Deg. C.
Recommended application temperature	+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>2	Hours
Shelf life	12	Months

Test Methods: BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568 6797