

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 1 Issued May 2015

3571F TRANSFER FINGERLIFT TAPE, ACRYLIC ADHESIVE -RED "REMOVE TO EXPOSE" Liner

| <u>TECHNICAL DETAILS</u> | <u>TYPICAL VALUE</u> | <u>UNITS</u> |
|-------------------------------------|----------------------|--------------|
| Thickness, adhesive only | 0.020 | mm |
| Release liner thickness | 0.055 | mm |
| 180 degree peel adhesion: | 350 | N/m |
| Polyester loop tack: | 400 | N/m |
| Liner release | 20 | N/m |
| Service temperature | -20 to +120 | Deg. C. |
| Recommended application temperature | +5 to +25 | Deg. C. |
| Shear adhesion, 1Kg @ 23 deg. C. | >24 | Hours |
| UV Resistance | Good | |
| Shelf life | 12 | Months |

Test Methods: BS 7116

Adhesive conforms to FDA Regulation 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN
UK. Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797