

PRODUCTS TECHNICAL DATA

Product datasheet Issue No. 4 Issued Mar 2016

RA 8030 DOUBLE-SIDED HIGH PERFORMANCE WHITE PVC FILMIC TAPE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.275	mm
Release liner thickness	0.66	mm
180 degree peel adhesion:		
Open side	1200	N/m
Liner side	1200	N/m
Polyester loop tack:		
Open side	1250	N/m
Liner side	1250	N/m
Liner release	3	N/m
Tensile strength	2000	N/m
Elongation at break	75	%
Static shear, 23 deg. C, 1Kg, 25mm square	>100	h.
23 deg. C, 2 Kg 25mm square	55	h.
Shear adh. failure temperature, 100g load	>100	deg. C.
250g load	>100	deg. C.
Minimum application temperature	10	deg. C.
Service temperature	-20 to +120	deg. C.
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568 - 6797