

# PRODUCTS TECHNICAL DATA

Product datasheet Issue No 4 Issued Oct 15

## RA 8057 DOUBLE-SIDED POLYESTER FILMIC TAPE SOLVENT ACRYLIC ADHESIVE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.100	mm
180 degree peel adhesion: Open side	600	N/m
Closed side	600	N/m
Polyester loop tack: Open side	800	N/m
Closed side	800	N/m
Liner release	10	N/m
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-40 to +140	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	>72	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN UK.

Email: [sales@paladhesives.co.uk](mailto:sales@paladhesives.co.uk)

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568-6797