

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No. 1 Issued Mar 14

2431F TRANSFER FINGERLIFT TAPE, 50gsm LINER (for lengths upto 3000mtrs)

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive only		0.025	mm
Release liner thickness		0.040	mm
180 degree peel adhesion:	Open side	800	N/m
Polyester loop tack:	Open side	900	N/m
Liner release		20	N/m
Service temperature		-10 to +60	Deg. C.
Recommended application temperature		+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		Greater than 100	Hours
Shelf life		12	Months
Test Methods: BS 7116			
Adhesive conforms to FDA Regulation 175.105			

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN, U.K

Telephone : +44 (0)121-5255151 Fax : +44(0)121-5686797

E-mail : sales@paladhesives.co.uk