

# 2000 SERIES

## TECHNICAL DATA



PAL ADHESIVE  
PRODUCTS Ltd

Product datasheet Issue No. 2 Issued Dec 2015

### RA 2732 ZCA DOUBLE SIDED GENERAL PURPOSE TISSUE TAPE

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

Adhesive Type : Pressure Sensitive Hot Melt / Rubber Resin

Thickness, adhesive + carrier

0.105

mm

Release liner thickness

0.105

180 degree peel adhesion:    Open side

1100

N/m

  Closed side

1100

N/m

Polyester loop tack:            Open side

1200

N/m

  Closed side

1200

N/m

Liner release

10

N/m

Tensile strength

1100

N/m

Elongation at break

4

%

Service temperature

-40 to +60

Deg. C.

Recommended application temperature

+5 to +25

Deg. C.

Shear adhesion, 1Kg @ 23 deg. C.

24

Hours

Shelf life

12

Months

Test Methods: BS 7116

BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd Wednesbury, WS10 7SG UK.

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797