

3000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Product datasheet Issue No 1 Issued July 2015
RA3515 DOUBLE-SIDED HIGH COAT WEIGHT TISSUE TAPE
PURE ACRYLIC ADHESIVE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive + carrier	0.115	mm
Release liner thickness	0.07	mm
180 degree peel adhesion: Open side	600	N/m
Closed side	600	N/m
Polyester loop tack: Open side	650	N/m
Closed side	650	N/m
Liner release	10	N/m
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-20 to +140	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	20	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd industrial Estate, Darlaston Rd Wednesbury, WS10 7TN UK.
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151 Fax: +44(0)121- 568-7152