

# PRODUCTS *TECHNICAL DATA*

Issue No 1 Issued October 2011

## RAS 76152 FOAM ANTI HOTSPOT TAPE FOR POLYTHENE TUNNEL GREENHOUSES

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive only	0.080	mm
Standard Foam thicknesses	3	mm
180 degree peel adhesion:	600	N/m
Polyester loop tack:	800	N/m
Liner release	10	N/m
Tensile strength	1000	N/m
Elongation at break	4	%
UV resistance	Excellent	
Service temperature	-20 to +70	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	100	Hours
Shelf life	12	Months
Test Methods		BS 3924

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN UK.  
Email: sales@paladhesives.co.uk  
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797