

FOAM & SPECIALITY

PRODUCTS TECHNICAL DATA

Issue No 2 Issued October 2004

RAS 76152 FOAM ANTI HOTSPOT TAPE FOR POLYTHENE TUNNEL GREENHOUSE

TECHNICAL DETAILS

TYPICAL VALUE

Thickness, adhesive only	0.080
Standard Foam thicknesses	4
180 degree peel adhesion:	400
Polyester loop tack:	800
Liner release	10
Tensile strength	1000
Elongation at break	MD - 130
UV resistance	Excellent
Service temperature	-20 to +70
Recommended application temperature	+5 to +25
Shear adhesion, 1Kg @ 23 deg. C.	100
Shelf life	12
Test Methods	

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind Estate, Darlaston Road, Wednesbury
Email: sales@paladhesives.co.uk
Tel: +44 (0)121 - 526 5151

Fax: +44(0)121 - 526 5152



**PAL ADHESIVE
PRODUCTS Ltd**

ES

UNITS

mm

mm

N/m

N/m

N/m

N/m

%

Deg. C.

Deg. C.

Hours

Months

BS 3924

ury, WS10 7TN UK.

21- 568 6797