

PRODUCTS TECHNICAL DATA

Issue No. 9

Issued January 2009

RA 8069 DOUBLE-SIDED TISSUE TAPE SOLVENT ACRYLIC ADHESIVE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness adhesive and carrier	0.095	mm
Release liner thickness	0.12	mm
Total Thickness	0.215	mm
Release liner type	White Polythene-coated kraft	
180 degree peel adhesion: Open side	700	N/m
Liner side	700	N/m
Polyester loop tack: Open side	1000	N/m
Liner side	1000	N/m
Liner release	10	N/m
Tensile strength	1000	N/m
Elongation at break	4	%
Shear adhesion, 1Kg @ 23 deg. C	>80	Hours
Temperature exposure short term	200 <1min	Deg. C.
Service temperature	-40 to +140	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR DETERMINING THE
SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.

