

# PRODUCTS TECHNICAL DATA

Product datasheet Issue No 1 Issued Nov 16

## T16.16 DOUBLE-SIDED TISSUE TAPE SOLVENT ACRYLIC ADHESIVE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.15	mm
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	700	N/m
Closed side	700	N/m
Polyester loop tack:		
Open side	800	N/m
Closed side	800	N/m
Liner release	10	N/m
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature, continuous	-40 to +140	Deg. C.
Temperature exposure short term	200 < 1min	Deg. C
Plasticizer Resistance		Excellent
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	50	Hours
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.

