

3000 SERIES

TECHNICAL DATA



Product datasheet Issue No 3 Issued May 21

RA 3073 DOUBLE-SIDED POLYPROPYLENE FILMIC TAPE MODIFIED EMULSION ACRYLIC ADHESIVE, WHITE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Thickness, adhesive + carrier	0.070	mm
Release liner thickness	0.055	mm
180 degree peel adhesion: Open side	750	N/m
Closed side	750	N/m
Polyester loop tack: Open side	850	N/m
Closed side	850	N/m
Liner release	65	gsm
Tensile strength	2200	N/m
Elongation at break	75	%
Service temperature	-20 to +100	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	20	Hours
Shelf life	12	Months
Test Methods: BS 7116		

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Road Ind. Estate, Darlaston Road, Wednesbury, WS10 7TN U

Email: sales@paladhesives.co.uk

Tel: +44 (0)121 - 526 5151

Fax: +44(0)121- 568 6797