

2000 SERIES

TECHNICAL DATA



PAL ADHESIVE
PRODUCTS Ltd

Issue No. 3

Issued Mar 2021

RA 2019 HIGH PERFORMANCE DOUBLE-SIDED TISSUE TAPE

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive System	Pressure Sensitive Hot Melt Rubber Resin	
Thickness, adhesive + carrier	0.130	mm
Release liner thickness	0.055	
180 degree peel adhesion: Open side	1200	N/m
Closed side	1200	N/m
Polyester loop tack: Open side	1300	N/m
Closed side	1300	N/m
Liner release	65	gsm
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	50	Hours
Shelf life	12	Months
UV Resistance	Poor	

Test Methods: BS 7116

The individual ingredients of the adhesive have been tested and approved for indirect food contact to the FDA specification 175.105

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.




PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN, UK.

✉ sales@paladhesives.co.uk  www.paladhesives.co.uk

☎ +44 (0)121 - 526-5151

 +44(0)121- 568-6797