

# 2000 SERIES

## TECHNICAL DATA



Product datasheet Issue No 7 Issued Jan 16

### RA 2056 DOUBLE-SIDED HIGH TACK TISSUE TAPE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Adhesive Type	Pressure Sensitive Hot-Melt Rubber Resin	
Thickness, adhesive + carrier	0.085	mm
Release liner thickness	0.055	mm
180 degree peel adhesion:		
Open side	1100	N/m
Closed side	1100	N/m
Polyester loop tack:		
Open side	1000	N/m
Closed side	1000	N/m
Liner release	65	gsm
Tensile strength	1000	N/m
Elongation at break	4	%
Service temperature	-40 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	> 50	Hours
Shelf life	12	Months
Test Methods: BS 7116		
Standard fingerlift formats	6/12, 9/15, 12/18, 18/24, 24/30 Other formats, inc. offset fingerlift available subject to min. quantities	

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR  
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE  
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN, UK.

✉ sales@paladhesives.co.uk 🌐 www.paladhesives.co.uk

☎ +44 (0)121 - 526-5151

☎ +44(0)121- 568-6797