

2000 SERIES

TECHNICAL DATA



Product datasheet Issue No 10 Issued Jan 2020

RA 2735 DOUBLE-SIDED ECONOMY FINGERLIFT TISSUE TAPE, WHITE LINER

TECHNICAL DETAILS

TYPICAL VALUE

UNITS

Adhesive Type :	Pressure Sensitive Hot Melt / Rubber Resin	
Thickness, adhesive + carrier	0.080	mm
Release liner thickness	0.055	
180 degree peel adhesion:	Open side	N/A
	Closed side	N/A
Polyester loop tack:	Open side	1200
	Closed side	1200
Liner release	65	GSM
Tensile strength	1200	N/m
Elongation at break	10	%
Service temperature	-10 to +60	Deg. C.
Recommended application temperature	+5 to +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.	50	Hours
Shelf life	12	Months
Standard product formats	6/12, 9/15, 12/18, 18/24, 24/30 Other formats, inc. offset fingerlift available subject to min. quantities	
Test Methods		BS 7116

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



PAL ADHESIVE
PRODUCTS Ltd

Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN, UK.

✉ sales@paladhesives.co.uk 🌐 www.paladhesives.co.uk

☎ +44 (0)121 - 526-5151 📠 +44(0)121- 568-6797