



Product datasheet Issue No 2

Issued April 2020

## **RA 3220 PERM/PEEL FILMIC EMULSION ACRYLIC DOUBLE-SIDED TAPE, AMBER PAPER LINER**

TECHNICAL DETAILS		TYPICAL VALUE	<u>UNITS</u>
Thickness, adhesive + carrier Release liner thickness		0.050 0.075	mm mm
180 degree peel adhesio	n: Open side Closed side	400 150	N/m N/m
Polyester loop tack:	Open side Closed side	800 100	N/m N/m
Liner		80	gsm
Tensile strength		4600	N/m
Elongation at break		120	%
Service temperature		-20 TO +120	Deg. C.
Recommended application temperature		+5 TO +25	Deg. C.
Shear adhesion, 1Kg @ 23 deg. C.		>2	Hours
Shelf life		12	Months
Test Methods: BS 7116 F&DA Approval		175.105	

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR
DETEMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES.



Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN, UK.

☑ sales@paladhesives.co.uk @ www.paladhesives.co.uk

**2** +44 (0)121 - 526-5151



**=** +44(0)121-568-6797