# FOAM & SPECIALITY PRODUCTS TECHNICAL DATA

PAL ADHESIVE PRODUCTS Ltd

Product datasheet Issue No 1 Issued Nov 16

## 8075 DOUBLE-SIDED FINGER LIFT TISSUE TAPE SOLVENT ACRYLIC ADHESIVE

| TECHNICAL DETAILS | | TYPICAL VALUE | UNITS |
|---|---|---|---|
| Thickness, adhesive + carrier | | 0.15 | mm |
| Release liner thickness | | 0.055 | mm |
| 180 degree peel adhesion: | Open side | 700 | N/m |
| | Closed side | 700 | N/m |
| Polyester loop tack: | Open side | 800 | N/m |
| | Closed side | 800 | N/m |
| Liner release | | 10 | N/m |
| Tensile strength | | 1000 | N/m |
| Elongation at break | | 4 | % |
| Service temperature, continuous | | -40 to +140 | Deg. C. |
| Temperature exposure short term | | 200 < 1min | Deg. C |
| Plasticizer Resistance | | | Excellent |
| Recommended application temperature | | +5 to +25 | Deg. C. |
| Shear adhesion, 1Kg @ 23 deg. C. | | 50 | Hours |
| Shelf life | | 12 | Months |

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR

PAL ADHESIVE PRODUCTS Ltd
Darlaston Rd Industrial Estate, Darlaston Rd, Wednesbury, WS10 7TN, UK.
sales@paladhesives.co.uk www.paladhesives.co.uk
+44 (0)121 - 526-5151 +44(0)121- 568-6797